

SUGGESTED MOUNTING HEIGHTS FROM FLOOR TO BOTTOM OF DRYER

MEN	WOMEN	TEENAGERS	CHILDREN	HANDICAPPED
45"(114cm)	43"(109cm)	41"(104cm)	35"(89cm)	37"(94cm)

Ι	UNITS ARE AVAILABLE AS SPECIFIED IN:				
	120V	8 AMP.	60 Hz		
	208-240V	4 AMP.	60 Hz		
	230V	3.9 AMP.	50/60 Hz		

MODEL NO.: TS-ABS COVER FINISH: WHITE POLYMER (ABS) MOUNTING: SURFACE TIME CYCLE: AUTOMATIC SENSOR ACTIVATED DRYER TYPE: HAND DRYER

NOTES:

836-056

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. ALL DIMENSIONS ARE CONSIDERED TRUE AND REFLECT MANUFACTURER'S SPECIFICATIONS.
- 3. DO NOT SCALE DRAWING.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info REFERENCE NUMBER 836-056.

THINAIR® HAND DRYER

THINAIR® HAND DRYER